CERTIFICATE OF MAILING

Libereby certify that this correspondence is being deposited with the United States Postal Service as First Class Mail in an envelope addressed to:

"Assistant Commissioner for Patents Washington, D.C. 20231"

on August 3, 2004.

KEVIN J. STEIN

Reg. No. 47,966

Attorney for Applicant(s)

<u>PATENT</u> #03-0221-UNI Case #J3676(C) IFW

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:

Chuah et al.

Serial No.:

10/603,318

Filed:

June 25, 2003

For:

COSMETIC COMPOSITIONS

Edgewater, New Jersey 07020 August 3, 2004

SUBMISSION OF PRIORITY DOCUMENT

Assistant Commissioner for Patents Alexandria, VA 22313-1450

Sir:

Pursuant to rule 55(b) of the Rules of Practice in Patent Cases, Applicant(s) is/are submitting herewith a certified copy of the United Kingdom Application No. 0214805.4 filed June 26, 2002, upon which the claim for priority under 35 U.S.C. § 119 was made in the United States.

It is respectfully requested that the priority document be made part of the file history.


Respectfully submitted,

Kevin J. Stein

Reg. No. 47,966

Attorney for Applicant(s)

KJS/mt (201) 840-2394









CERTIFIED COPY OF PRIORITY DOCUMENT

The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save or the substitution as, or inclusion as, the last part of the name of the words "public limited ompany" or their equivalents in Welsh, references to the name of the company in this certificate ad any accompanying documents shall be treated as references to the name with which it is so registered.

accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, C. or PLC.

egistration under the Companies Act does not constitute a new legal entity but merely cts the company to certain additional company law rules.

Signed

Dated

12 June 2003



Patents Act 1977 16)

you fill in this form)

2.

5.

The **Patent Office**

27JUN02 E728958-7 D02898. .P01/7700 0.00-0214805.4

THE PATENT OF 26 JUN 2002

J3676(C)/ijh

The Patent Office

Cardiff Road Newport Gwent NP10 8QQ

1. Your reference

Request for grant of a patent

(See the notes on the back of this form. You can also get

an explanatory leaflet from the Patent Office to help

Patent application number

0214805.4

26 JUN 2002

1628002

Full name, address and postcode of the or of 3.

(The Patent Office will fill in this part)

each applicant (underline all surnames)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

UNILEVER PLC UNILEVER HOUSE, BLACKFRIARS **LONDON, EC4P 4BQ**

COSMETIC COMPOSITIONS

UNITED KINGDOM

Title of the invention 4.

"Address for Service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Patents ADP number (if you know it)

Name of your agent (if you have one)

PEARCE, Timothy

PATENT DEPARTMENT, UNILEVER PLC **COLWORTH HOUSE, SHARNBROOK BEDFORD, MK44 1LQ**

67834671201

If you are declaring priority from one or more 6. earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number (if you know it)

Date of filing (day / month / year)

If this application is divided or otherwise 7. derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing (day/month/year)

Is a statement of inventorship and of right 8. to grant of a patent required in support of this request? (Answer 'Yes' if:

- any applicant named in part 3 is not an inventor, or
- there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body. See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	40	
Claim(s)	6	A
Abstract	1	1
Drawing(s)	1 1	

10. If you are also filing any of the following, state how may against each item.

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents

(please specify)

I/We request the grant of a patent on the basis of this application.

Sandra Jane EDWARDS, Authorised Signatory

Signature(s)

1

Date: 26/06/02

12. Name and daytime telephone number of person to contact in the United Kingdom

ISOBEL HOWELL, Tel 01234 22 2082

11.

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes


- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505. a)
- Write your answers in capital letters using black ink or you may type them. b)
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper c) and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it. e)
- f) For details of the fee and ways to pay please contact the Patent Office.

10

15

20

25



Cosmetic Compositions

The present invention relates to cosmetic compositions, especially compositions intended for topical application to the body containing an antiperspirant and particularly to compositions in the form of soft solids.

Background and prior art

Cosmetic compositions containing an antiperspirant that are intended for topical application to the body are available to the public in a number of product forms, of which one form that has been popular in the last 10 years is that of soft solids. These have sometimes alternatively been referred to as semi-solids or as In essence, and irrespective of the anhydrous creams. name used, the soft solid comprises a particulate antiperspirant active that is dispersed within a waterimmiscible carrier fluid that is structured by one or more structurants. It is commonly stored in a dispensing container which comprises a product chamber, usually a round or oval cylinder, having at one end a cover defining a number of apertures through which the contents of the chamber can be dispensed and a means to expel the contents through the apertures. That means can comprise squeezable side-walls, or more commonly a platform or elevator at an intermediate position within the cylindrical chamber that can be advanced towards the first end.

30

In order for the soft solid to be dispensed through the aperture(s) in the cover of the chamber, the rheological properties of the composition are altered when it is subjected to mild pressure and especially in the vicinity

of the aperture wall compared with the normal state that existed prior to the soft solid being extruded under pressure through those apertures. When pressurised and extruded through the aperture, the micro-structure of the 5 solidified carrier liquid is partly destroyed adjacent to its contact boundary with the aperture, so that the viscosity of the composition is locally reduced, thereby enabling the composition to flow. This subsequently 10 becomes especially noticeable in the vicinity of the apertures through which the composition is being The micro-structure of the composition that dispensed. has been extruded through the apertures or that remains within or close to the apertures may often not reform to 15 a significant extent or at best reform only extremely slowly when the pressure on the composition is released, with the result that after the composition has been subjected to pressure and partial extrusion, it still has a lower viscosity in the vicinity of the cover apertures. 20 Indeed, a separate localised liquid phase can be formed, particularly from one or more of the oils in which particulate materials are suspended. An undesired consequence of the formation of a separate liquid phase is a problem called syneresis, in which the liquid phase, 25 particularly the oils, can seep out of the chamber, or possibly be expelled from the chamber as a consequence of residual or subsequent pressure in the container, onto the surface of the dispensing container, and possibly trickling down the sides of the container.

30

Although damage to the microstructure of the soft solid occurs at the time of extrusion through the cover apertures, the appearance of the oils or other liquid on the surface tends to be retarded, because it takes a

finite period of time for transfer of fluid from within the container. Thus, the extent of liquid on the container surface tends to increase for a period of maybe half an hour to 2 or 3 hours after the product has been 5 dispensed (and applied topically to the armpit) depending on the oils and the structurants employed. Thereafter, there tends to be little, if any, additional egress of However, once the oil has egressed, there is no mechanism for its subsequent recapture by the remaining 10 composition within the container. Moreover, since the problem of syneresis does not occur instantly, but develops during the period of at least half an hour later, the consumer normally does not have an opportunity to take remedial action by wiping the container after the 15 oils have appeared. If wiping were done shortly after use, the problem would materialise subsequently. Consequently, whether on the top or sides, the oils can form a sticky and often unsightly mess, possibly after partial evaporation. This is not liked by consumers who 20 wish to use dispensers that are not sticky to hold or unsightly to view.

Consequently, in one respect, the problem that the
instant invention seeks to address is how to formulate a
soft solid composition so that the problem of syneresis
is eliminated or at least ameliorated.

One strategy that has been proposed by some patentees to combat the problem of syneresis comprises incorporating a pressure-relief mechanism that forms part of or is linked to the mechanism that expels soft solid out of the dispenser comprises means to reduce the extent of pressure generation in the dispenser for soft solids.

These mechanisms can include suck-back mechanisms to automatically partially withdraw the elevator or platform away from the cover immediately subsequent to its 5 advancement, thereby increasing the volume available for the soft solid within the dispenser between the platform and top wall and accordingly reducing the pressure immediately. A second means which mitigates the problem by increasing the ratio of the volume of composition that 10 is extruded relative to the aperture sidewall length comprises increasing the proportion of apertures in the top wall. The two means may be employed together. A-6143 284). However, a pressure release mechanism mentioned above can render more complicated the advance mechanism, and increase the cost of the dispenser, which 15 already can constitute a very significant proportion of the total, cost of the product. Furthermore, it does not address the fundamental question of how to reduce the inherent susceptibility of the composition to syneresis.

20

25

30

The problem of its syneresis is not the only problem that is potentially associated with a soft solid composition. In the course of investigating the suitability of a number of antiperspirant compositions to carry out their intended purpose, the instant inventors have recognised that changes to the constitution of the carrier liquid and structurants can not only alter the susceptibility or resistance of the composition to syneresis, but can simultaneously impair the inherent capability of the suspended antiperspirant to control perspiration when the composition has been applied topically onto human skin, such as in axilary regions. Moreover, any resultant composition still needs to be capable of being dispensed through the top wall of the dispenser when subjected to

20

mild pressure. Accordingly, the problem faced by the instant inventors was to devise soft solid compositions that not only enjoyed an improved inherent resistance to syneresis, whilst simultaneously remaining dispensable, but at the same time also maintaining an acceptable capability to control perspiration.

Summary of the invention

- 10 According to a first aspect of the present invention, there is provided
 - a cosmetic composition comprising;
 - at least 60% by weight in total of a water immiscible carrier liquid and structurant system therefor, and from 1 to 30% by weight of a particulate antiperspirant active suspended in said carrier liquid said carrier liquid comprising a mixture of a hydrocarbon oil and an aromatic ester oil in a weight ratio of from 1:2 to 15:1 and said structurant system comprising from 5.5 to 20% in total of a di or triblock alkylene/arylene block copolymer and an organic wax in a weight ratio to each other of from 5:1 to 30:1.
- 25 The present invention is founded upon the provision simultaneously of not only a carrier liquid which is a mixture of two essential components, namely the hydrocarbon oil and the aromatic ester oil but also a combination of the organic wax and the hydrocarbon block copolymer. By so selecting the carrier oil mixture and the combination of structurants specified above, it is possible to create an anhydrous antiperspirant composition that displays an enhanced resistance to syneresis even through dispensers which do not contain

means to limit syneresis and which maintains an acceptable capability to control perspiration. The invention compositions can also exhibit further beneficial properties, such as desirable sensory properties, reducing or eliminating visible deposits on the skin or being translucent, depending upon the choice of the individual constituents and their proportions.

- According to a second aspect of the present invention there is provided a cosmetic product comprising an anhydrous soft solid cosmetic composition contained within a dispensing container comprising a chamber for the cosmetic composition provided at one end with a closure defining at least one aperture and with a means for impelling the cosmetic composition towards the closure, in which the cosmetic composition is in accordance with the first aspect of the present invention. Suitably, the dispensing container is free from immediate pressure reducing means.
- According to a third aspect there is provided a process of making a cosmetic product comprising a dispensing container comprising a chamber for a cosmetic composition provided at one end with a closure defining at least one aperture and with a means for impelling the antiperspirant composition towards the closure, characterised in that the cosmetic composition is in accordance with the first aspect, and the process comprises the steps of
 - i) forming a mixture of the organic wax and at least a fraction or component of the carrier fluid mixture comprising hydrocarbon oil and/or aromatic ester oil;

25

30

- ii) stirring the mixture and raising its temperature to a temperature selected within the range of from 50 to 120°C at which the mixture is homogeneous;
- 5 iii) introducing into the mixture the copolymer, optionally premixed with the remainder of the carrier liquid, stirring the augmented mixture and maintaining or elevating its temperature within the range of up to 120°C until it is homogeneous;
- 10 iv) introducing the particulate antiperspirant with stirring into the homogenous augmented mixture at a temperature above its normal setting temperature;
 - v) introducing the resultant antiperspirant-containing mixture into the chamber of the dispenser and
- vi) cooling the antiperspirant-containing composition or allowing it to cool to below a temperature at which it forms a soft solid.

Detailed description of the invention and preferred embodiments.

The present invention relates to a cosmetic composition containing a particulate antiperspirant active, a combination of selected oils in desired proportions forming a water-immiscible carrier liquid that is structured by a combination of a specified block copolymer and an organic wax. Herein such a composition can be referred to as an antiperspirant composition. The individual constituents of the composition and preferred embodiments of the invention will now described in greater detail, as well as a number of optional constituents, the incorporation of each of which can result in desirable or preferred compositions.

Antiperspirant Actives

The composition preferably contains an antiperspirant active. Antiperspirant actives, are preferably incorporated in an amount of from 0.5-60%, particularly from 5 to 30% or 40% and especially from 5 or 10% to 30 or 35% of the weight of the composition.

Antiperspirant actives for use herein are often selected from astringent active salts, including in particular aluminium, zirconium and mixed aluminium/zirconium salts, including both inorganic salts, salts with organic anions and complexes. Preferred astringent salts include aluminium, zirconium and aluminium/zirconium halides and halohydrate salts, such as chlorohydrates and activated aluminium chlorohydrates.

Aluminium halohydrates are usually defined by the general formula Al²(OH)^xQ^y.wH²O in which Q represents chlorine,

bromine or iodine, x is variable from 2 to 5 and x + y = 6 while wH²O represents a variable amount of hydration.

Especially effective aluminium halohydrate salts, known as activated aluminium chlorohydrates, are described in EP-A-6739 (Unilever NV et al), the contents of which

specification is incorporated herein by reference. Some activated salts do not retain their enhanced activity in the presence of water but are useful in substantially anhydrous formulations, i.e. formulations which do not contain a distinct aqueous phase.

Zirconium actives can usually be represented by the empirical general formula: $ZrO(OH)^{2n-nz}B^z.wH^2O$ in which z is

a variable in the range of from 0.9 to 2.0 so that the value 2n-nz is zero or positive, n is the valency of B, and

B is selected from the group consisting of chloride, other halide, sulphamate, sulphate and mixtures thereof.

Possible hydration to a variable extent is represented by wH²0. Preferable is that B represents chloride and the variable z lies in the range from 1.5 to 1.87. In practice, such zirconium salts are usually not employed by themselves, but as a component of a combined aluminium and zirconium-based antiperspirant.

The above aluminium and zirconium salts may have coordinated and/or bound water in various quantities and/or
may be present as polymeric species, mixtures or
complexes. In particular, zirconium hydroxy salts often
represent a range of salts having various amounts of the
hydroxy group. Zirconium aluminium chlorohydrate may be
particularly preferred.

Antiperspirant complexes based on the above-mentioned astringent aluminium and/or zirconium salts can be employed. The complex often employs a compound with a carboxylate group, and advantageously this is an amino acid. Examples of suitable amino acids include dl-tryptophan, $dl-\beta$ -phenylalanine, dl-valine, dl-methionine and β -alanine, and preferably glycine which has the formula $CH^2(NH^2)COOH$.

30

25

It is highly desirable to employ complexes of a combination of aluminium halohydrates and zirconium chlorohydrates together with amino acids such as

glycine, which are disclosed in US-A-3792068 (Luedders et al). Certain of those Al/Zr complexes are commonly called ZAG in the literature. ZAG actives generally contain aluminium, zirconium and chloride with an Al/Zr

ratio in a range from 2 to 10, especially 2 to 6, an Al/Cl ratio from 2.1 to 0.9 and a variable amount of glycine. Actives of this preferred type are available from Westwood, from Summit and from Reheis.

Other actives which may be utilised include astringent titanium salts, for example those described in GB 2299506A.

15

10

5

The proportion of solid particulate antiperspirant salt in a suspension composition normally includes the weight of any water of hydration and any complexing agent that may also be present in the solid active.

20

25

30

The antiperspirant active may comprise such salts or mixture of such salts by themselves, but may alternative comprise a combination of such salts with a water-soluble polymer comprising Br nsted acid groups that acts as a co-gellant for the antiperspirant salt when mixed therewith in the presence of water, preferably in a weight ratio of the salt to the polymer of from 25:1 to 1:10. Preferably, the polymer is an organic polymer possessing a carbon backbone, optionally interrupted by ester or amide groups and having less than 50 mole % of positively-charged monomer units. The polymer very desirably comprises carboxylic acid groups or precursor thereof, and particularly has an acid value of greater than 160, for example being derivable from maleic acid or

15

20

25

30

anhydride monomer. If employed, the polymer is normally present in discrete particles.

5 The composition takes the form of a suspension in which antiperspirant active in particulate form is suspended in

the water-immiscible liquid carrier. Antiperspirant composition according to the present invention do not have any separate aqueous phase present and may conveniently be referred to as "anhydrous" although it should be understood that some water may be present bound to the antiperspirant active or as a small amount of solute within the water-immiscible liquid phase. In such compositions, the particle size of the antiperspirant salts often falls within the range of 0.1 to 200 μ m with a mean particle size often from 3 to 30 μ m. Actives having either larger or smaller mean particle sizes can also be contemplated such as from 30 to 50 μ m or 0.1 to 3 μ m.

The particulate antiperspirant active may be present in the form of hollow spheres or dense particles (by which is meant particles which are not hollow) at the discretion of the manufacturer. Where it is desired that the composition is translucent in bulk or to reduce the appearance of visible deposits on the skin to which the composition is applied or on clothing which comes into contact with the composition, it is preferable for the particles to be substantially free from hollows. As has previously been described, hollows can be eliminated by crushing the spheres. Furthermore for translucent bulk compositions, it is highly desirable to employ actives having no greater than a minor weight proportion of

particles of below 10 μm diameter, for example by selecting an active having a mean particle size of from 12 to 30 μm diameter.

5

25

30

Carrier liquid

The water-immiscible carrier liquid herein comprises a mixture of materials which are relatively hydrophobic so as to be immiscible in water. The invention employs 10 essentially, in combination, at least one hydrocarbon oil and at least one aromatic ester oil. It will generally be desired that this carrier mixture is liquid (in the absence of structurant) at temperatures of 15°C and 15 above. It may have some volatility but its vapour pressure will often be less than 4kPa (30 mmHg) at $25^{\circ}C$ so that the material can be referred to as a mixture of oils. More specifically, in most embodiments at least 50% by weight and in a number of embodiments at least 80% by weight of the hydrophobic carrier liquid consists of 20 materials with a vapour pressure not over this value of 4kPa at 25°C.

The hydrocarbon oils which can be incorporated in compositions herein include liquid aliphatic hydrocarbons such as mineral oils or hydrogenated polyisobutene, often selected to exhibit a low viscosity. Further examples of liquid hydrocarbons are polydecene and paraffins and isoparaffins of at least 10 carbon atoms and in many instances up to about 35 carbons. Many suitable liquid hydrocarbons contain from 12 to 25 carbons. Highly desirable results have been achieved employing a mineral oil and/or an isoparaffin. The hydrocarbon oil may be

15

20

25

30

introduced at least in part as a carrier for one of the other constituents of the composition, such as the copolymer and/or may be introduced by itself.

In the essential liquid aromatic ester oils herein, the alkanol and acid residues or mixtures thereof are

preferably selected such that the ester oils each have a melting point of below 20°C.

Suitable liquid aromatic esters for use in the compositions described herein can comprise esters derived from an aryl alcohol and an aryl acid, ie both moieties are aryl or esters in which one of the moieties is aryl and the other is alkyl, provided that they have a melting point that enables them to be a liquid at ambient temperature. Suitable esters include aryl benzoates of melting point at or below ambient temperature, for example benzyl benzoate. Preferred esters include fatty alkyl benzoate, alkyl or dialkyl naphthalate or fatty alkyl salicylate esters, and especially fatty alkyl benzoates. Examples of such esters include suitable C⁸ to C18 alkyl benzoates or mixtures thereof, including in particular C12 to C15 alkyl benzoates eg those available under the trademark Finsolv. Others include linear or branched C¹⁰ to C¹⁸ salicylate esters, eg butyloctyl salicylate. Such materials are commonly monoesters. They are particularly suitable for use herein. Yet others are dialkyl diesters eg C^6 to C^{12} diesters of naphthalic acid, eg diethylhexyl-2,6-naphthalate.

10

15

Especially desired combinations of oils herein comprise a mixture of a mineral oil and/or an iso-paraffin oil with an alkyl benzoate (monoester), such as any of each described hereinabove.

The hydrocarbon and aromatic ester oils are employed herein in a weight ratio of 1:2 to 15:1, preferably in a weight ratio of at least 2:3 and particularly at least 1:1. In many suitable mixtures, the weight ratio is up

to 10:1, in a number of desirable mixtures at up to 6:1 and especially at up to 4:1. Such weight ratios herein are based on the total weights of oils that are introduced, ie the total of oils that are introduced by themselves plus any amount from a premix or predispersion, for example if or when it is acting as a carrier for some other constituent.

The total weight proportion of the carrier oils of the composition is usually selected in at least 45% and particularly at least 55%. In many embodiments, their total weight proportion is not more than 80% and in some preferred embodiments, is not more than 70%.

25

30

It is especially desirable in some embodiments to select a blend of carrier oils together with the antiperspirant active to achieve a near mis-match between the mean Refractive Index of the carrier oil blend and that of the antiperspirant active, for example within 0.06 and in many instances within 0.05 units, avoiding the need for close matching of the refractive indexes (RIs, eg to within 0.003 units). The difference in RI of the particulate antiperspirant and the carrier fluid in such

10

15

embodiments is usually greater than 0.005 and commonly greater than 0.01 units. Such a respective near mismatch can be achieved readily by employing a aluminium chlorohydrate or activated aluminium chlorohydrate an antiperspirant active together with the entire range of blends of oils described above, or by employing an RI modified aluminium zirconium complex, the RI of which has been reduced to about 1.54 or lower, such as by a water treatment (hydration). The antiperspirant active is very preferably free from hollow particles, as indicated

hereinbefore. The choice of a near mis-match rather than close matching renders the formulation more tolerant to small changes in the constituents and their proportions which can arise during manufacturing on a bulk scale.

Structurant system

Herein the structurant system employed comprises a combination of an organic wax and a di and/or tri block 20 alkyl/aryl copolymer. The combined weight of the structurant system is usually at least 5.5%; in many preferred embodiments the structurant system is up to 12% In a number of desirable embodiments, at by weight. least 6% by weight of the structurant system is employed. 25 In various particularly suitable embodiments not more than 9% by weight of the structurant system is employed. The weight ratio of the organic wax to the block copolymer is usually at least 6:1 and often is at least 8:1. In many suitable embodiments, its weight ratio is 30 up to 24:1 and especially is up to 16:1. To some extent, it is desirable to vary the weight proportion of the copolymer inversely to that of the organic wax, for example selecting the weight proportions of both

10

components of the system such that the numerical product obtained by multiplying the weight proportion of organic wax with the weight proportion of the copolymer falls in the range of from 4 to 6.5.

Organic wax

This term "organic wax" is applied herein to a variety of organic materials including mixtures which have similar physical properties, namely that:-

they are solid at 30°C and preferably also at 40°C ;

they melt to a mobile liquid at a temperature above 30°C but generally below 95°C and

preferably in a temperature range of 40° C to 90° C;

they are water-insoluble and remain waterimmiscible when heated above their melting point.

Accordingly, the term organic wax comprises not only
natural waxes, which traditionally were derived from
plant material, possibly via concentration by bees, but
also synthesised waxes and other organic materials that
are waxy and thus resemble waxes.

Organic waxes are usually hydrocarbon waxes, waxy linear fatty alcohols, waxes comprising esters of fatty acids or mixtures containing such compounds along with a minority (less than 50%) of other compounds. Naturally occurring waxes are often mixtures of compounds which include a substantial proportion likely to be a majority of fatty esters.

Organic waxes form crystals in the water-immiscible liquid when it cools from the heated state during processing.

5

20

25

These crystals take various forms including needles and platelets depending on the individual waxes. Some waxes form a network of fibrous crystals.

10 Examples of hydrocarbon waxes include paraffin wax, ozekerite, microcrystalline wax and polyethylene waxes with molecular weight of 2,000 to 10,000.

Examples of ester waxes include esters of long chain fatty acids with glycerol or ethylene glycol, such as C^{18}
36 fatty acids or C^{16} - C^{22} fatty acids or individual fatty

acids such as linear saturated C^{18} or C^{22} acids. Such esters may be made synthetically and various triglyceride waxes are extractable from plants, as indicated below.

Examples of natural waxes include beeswax, carnauba, candelilla, and spermeceti waxes that are of vegetable origin and mineral waxes from fossil remains other than petroleum. Montan wax, which is an example of a mineral wax, includes non-glyceride esters of carboxylic acids, hydrocarbons and other constituents.

Other organic waxes comprise linear fatty alcohols,
normally monohydric and commonly fully saturated
containing from 14 to 24 carbons, of which suitable
examples include cetyl alcohol, stearyl alcohol,

eicosonyl alcohol and behenyl alcohol or mixtures of any two or more thereof.

- Organic waxes useful in the present invention will generally be those found to thicken water-immiscible oils such as mineral oil when dissolved therein (by heating and cooling) at a concentration of 5 to 15% by weight.
- Herein, organic waxes employed herein commonly crystallise on cooling to form spherulitic needles or small platelets, which are distributed through and impart structure to the carrier liquid. Castor wax is an example of waxes that often crystallise as needles.

Preferably, the weight of organic waxes in the composition is at least 5%, particularly at least 6%. In many desirable embodiments, its weight is not greater than 12%, and particularly up to 8.5% or 9%.

20

25

30

15

Block Copolymers

Herein, the structurant system comprises a minor proportion in relation to the above-mentioned organic wax of thermodynamically incompatible copolymers, by which is meant that the polymer contains two opposite and apparently incompatible segments, such as in particular one hard relatively insoluble and one soft relatively soluble segment. This can be provided by incorporating into the copolymer both an aryl polymer block (A) to provide the hard/insoluble segment and a polyalkylene block segment (B) to provide a soft/soluble segment. Each block commonly comprises at least 50 or at least 100 monomeric units. Such copolymers tend to provide a three-dimensional network which extends through out the

10

15

20

25

30

carrier liquid, through physical cross-links, possibly with the formation of relatively insoluble submicroscopic particles of the particular block, otherwise called domains. The copolymers can be linear.

The aryl monomer polymerised to form one segment A commonly comprises styrene, though alternative monomers comprising two or more fused rings can be used too. The polyalkylene segment B can be derived from butadiene, isoprene, ethylene/butylene and ethylene/propylene. Diblock copolymers have the form A-B and triblock copolymers preferably have the form A-B-A. The diblock and triblock copolymers can be employed separately or a mixture of both can be used.

The block copolymer can be introduced into the composition in the form of a pre-dispersion of the block copolymer in at least part of the carrier liquids.

Herein the term dispersion or pre-dispersion indicates

that the dispersed material is distributed throughout its carrier fluid, often in the form of discrete particulates but possibly at or approaching a molecular scale at or resembling a solution. This pre-dispersion can sometimes be obtained commercially in the form of a gel of the copolymer in a hydrocarbon oil. Such pre-formed gels, according to the manufacturers contain the range of from 1 to 20% by weight. The inventors have found it convenient to employ pre-formed gels which contain the copolymer itself in the region of 1.5 to 4% by weight. Various preformed gels are available from Aiglon under their trademark Transgel, from Penreco under their trademark Versagel and from Collaborative Laboratories

under their trademark Polysynlane Gel, in which the copolymer has gelled a hydrocarbon oil selected from a mineral oil, hydrogenated polyisobutene or isodecane.

Alternatively, a dispersion of the copolymer in a carrier oil system can be obtained by introducing the copolymer itself, into at least the hydrocarbon oil component of the carrier oil system, particularly at elevated temperature, such as from 70 to 102°C. Styrene/alkylene

10 block copolymers are commercially available under the trade mark Kraton, such as Kraton D and especially Kraton G, from Kraton Polymer Business.

The weight proportion of the block copolymer or mixture of block copolymers in the composition is commonly low, often being at least 0.4% and less than 2%. Preferably, the weight proportion of the copolymer is at least 0.5%. Often it is not necessary to employ more than 1.25% by weight of it.

20

One further way of identifying a suitable proportion of block copolymer to employ is by adjusting the amount of copolymer such that the viscosity of a dispersion of the polymer in the chosen amount of the carrier blend alone falls within a preferred range. Such a dispersion is obtained by forming a mixture of the copolymer and the carrier liquid or blend of liquids at an elevated temperature, eg 80 to 85°C and thereafter permitting the resultant mixture to cool to the temperature at which its viscosity is measured. Desirably, the resultant dispersion has a viscosity when measured at 25°C by a

viscometer, eg a RV20 Rotovisco ™ viscometer from Haake employing an SV1 cup and bob system, of at least 0.5 Pa.s, preferably at least 1 Pa.s, desirably up to 75 Pa.s, more desirably up to 50 Pa.s and even more desirably up to 25 Pa.s, viscosities measured at an applied shear stress of 15 Pa..

To some extent, the preferred proportion of structurant
system varies in line with the proportion of carrier oils
in the composition. It is often desirable to employ a
weight ratio of carrier oils to structurant system within
the range of from 6:1 to 10:1, particularly at least 7:1
and/or up to 9:1.

15

20

Optional Ingredients

Optional ingredients in compositions of this invention can include deodorants, for example at a concentration of up to about 10% w/w. Suitable deodorant actives can comprise deoperfumes, and/or microbicides, including particularly bactericides, such as chlorinated aromatics, including biguanide derivatives, of which materials known as Triclosan (Irgasan DP300 $^{\text{M}}$), Tricloban $^{\text{M}}$, and

25 Chlorhexidine warrant specific mention. A yet another class comprises biguanide salts such as available under the trade mark $Cosmosil^{m}$.

Other optional ingredients include wash-off agents, often present in an amount of up to 10% w/w to assist in the removal of the formulation from skin or clothing. Such wash-off agents are typically nonionic surfactants such as esters or ethers containing a C⁸ to C²² alkyl moiety

and a hydrophilic moiety which can comprise a polyoxyalkylene group (POE or POP) and/or a polyol.

The composition herein can incorporate one or more cosmetic adjuncts conventionally envisaged for antiperspirant soft solids. Such cosmetic adjuncts can include skin benefit agents such as glycerol, allantoin or lipids, for example in an amount of up to 5%; and soluble colorants. Skin cooling agents such as menthol and menthol derivatives, often in an amount of up to 2%, all of these percentages being by weight of the composition. A commonly employed adjunct is a perfume, which is normally present at a concentration of from 0 to 4% and in many formulations from 0.25 to 2% by weight of the composition.

The formulations can also include, if desired, a small particle sized inorganic thickener, often in an amount of from 0.1 to 2% by weight. Finely particulate silica, eg fumed silica, such as available as Aerosil™ 200 represents a preferred inorganic thickener.

In addition to the two above-identified essential

25 constituents of the liquid carrier, in some embodiments,

a minor fraction of the liquid carrier can comprise one or more auxiliary oils such as hydrophobic carrier oils selected from silicone oils, be they volatile and/or non-volatile, polymeric aliphatic ethers, and aliphatic esters. Such auxiliary oils have a melting point of not higher than 25°C commonly not above 20°C and a boiling point of not below 100°C.

Suitable volatile silicone oils comprise linear methicones and preferably cyclomethicones, usually containing from 4 to 7 silicon atoms, such as in particular D5. Examples include those available from Dow Corning Inc under their marks DC245 or DC345. Suitable non-volatile silicone oils commonly comprise linear alkyl/aryl methicones such as that available from Dow Corning Inc under their mark DC556 or DC704 and linear methicones of higher viscosity than volatile silicones such as those within the range available from Dow Corning Inc under their trademark DC200 having a viscosity of at least 10 centipoise (Pa.s).

15 Suitable polymeric aliphatic ethers include those ethers having a polypropylene glycol moiety of from 10 to 20 units terminated by a C4 to C6 aliphatic alcohol such as butanol, eg the ether referred to as PPG-14 butyl ether in the CFTA Handbook.

20

25

30

10

Suitable aliphatic esters contain at least one long chain saturated hydrocarbon group, eg an alkyl group, such as esters derived from C^1 to C^{20} alkanols, commonly monohydric alcohols, esterified with a C^8 to C^{22} alkanoic acid. The saturated hydrocarbon can be embedded within a C^6 to C^{10} alkanedioic acid or diol that is esterified by a

respective alkyl C^1 to C^{18} alkanol or carboxylic acid and especially a group containing ≥ 3 carbons. These esters include isopropyl myristate, lauryl myristate, isopropyl palmitate, diisopropyl sebacate and diisopropyl adipate. Suitable aliphatic esters commonly comprise at least one fatty moiety, such as an alkyl group of from 12 to 22

carbons linked via an ester linkage to a shorter chain length alkyl or alkylene moiety containing from 1 to 6 carbons. The aliphatic moieties can be linear or branched. Examples of triesters include triglycerides containing one $C^{12}-C^{25}$ alkyl substituent and two $C^{1}-C^{4}$ alkyl substituents.

The total proportion of such auxiliary oils is normally not greater than 15% by weight of the total weight of carrier oils, in many embodiments not greater than 10% and very desirably not greater than 5%.

The carrier liquid can include, if desired, a liquid

15 moisturising agent, such as a polyhydric humectant, of
which glycerol is preferred. The proportion of such
moisturising agent, if present, is often at least 0.5%,
commonly not more than 10%, and in many instances is from
1 to 6% by weight of the carrier. Alternatively, such
20 humectant can be bound with the antiperspirant salt.

It will be recognised that the compositions described herein do not mention by name various ingredients that have been contemplated in cosmetic or antiperspirant compositions published in literature, including patent specifications and journal articles. It is preferred to avoid incorporating each or any of such ingredients, or at least incorporate less than the proportion of such a

30 non-preferred ingredient given in such prior published compositions.

The compositions of the instant invention can be prepared by a convenient process in which the structurant system,

15

20

25

30

ie the organic wax and the copolymer, is dissolved or dispersed in the carrier fluid at a temperature above the melting point of the organic wax, the particulate antiperspirant active material is introduced into the mixture of carrier oils and structurant system and resultant composition is cooled to below its normal setting temperature, thereby forming a soft solid which can be caused to flow by the application of gentle pressure. The antiperspirant active is often introduced at a temperature intermediate between that at which the structurant system is dispersed in the carrier oils and that at which the composition sets, such as at a temperature in the range of about 1/3 rd to 2/3 rds above the setting temperature, for example, at about 65°C if the carrier oil/structurant mixture is formed at 80°C and the composition sets at $50^{\circ}C$.

The product (composition filled into a dispenser) can be made by introducing the composition whilst it is still mobile into the storage chamber of the dispenser through a filling aperture and thereafter closing the filling aperture. The filling aperture may be positioned at the dispensing end, ie top, of the dispenser barrel, and thereafter closed by fitting a top cover which is perforated by a number of dispensing apertures, optionally sealable by a cap, or positioned at the end opposite the dispensing end, ie bottom, of the barrel, and thereafter closed by inserting a close fitting

platform or piston into the barrel and mechanism to advance it towards the dispensing end.

The filling can be accomplished by a conventional pour technique in which the composition commonly is maintained at a temperature of about 5 to 10° C above its normal setting temperature and gravity fed through a nozzle into the dispenser. Alternatively, filling can be effected by injection under pressure as described in WOO1/76409, desirably at a temperature within -3° C to $+1^{\circ}$ C of the normal setting temperature of the composition.

10

The dispenser for applying the composition topically to the body, and particularly to underarm regions commonly comprises a storage chamber, often in the form of a tubular barrel having at one end a topwall, commonly 15 domed, that is penetrated by at least one dispensing aperture or a pattern of apertures in fluid communication with the storage chamber and a means disposed remote from the topwall that imparts pressure to the contents of the storage chamber and thereby impel it through the 20 dispensing aperture. Such means can comprise the chamber having at least one side or basewall that can be deformed inwardly thereby reducing the volume of the chamber, for example in the manner of a pouch or squeezable tube, eg as described in WO00/50314. In an alternative and more 25 conventional dispenser for antiperspirant formulations, such means comprises a close-fitting platform or piston that is located within a tubular barrel at the bottom of the storage chamber. The platform can be impelled towards the topwall manually, such as digitally, ie by a 30 finger inserted within the barrel through a base aperture, or by an advance mechanism in which the

10

15

20

platform is mounted on a spindle, typically via cooperating screw threads and the spindle is rotated, either by an externally mounted rotor wheel as in USP 5000356 or by a ratchet and pawl as in USP 5839622.

To a first approximation, and in the absence of pressurereducing means, the propensity of a given soft solid formulation to synerese in a dispensing container having dispensing apertures of similar size in its top wall is inversely related the proportion of the top wall surface area that the apertures occupy. Advantageously, the resistance of the formulations according to the instant invention to synerese enables them to be employed in dispensing containers that have a comparatively small area of its topwall penetrated by the dispensing aperture or apertures, such as below 14% without needing special pressure reducing means to mitigate or prevent syneresis. The dispensing apertures normally comprise at least 3% of the top wall surface area. In a number of suitable dispensers, the aperture proportion is from 3 to 13% of the top wall surface area.

The dispensing apertures need not be confined to a

25 central region and are can suitably be distributed across
the entire span of the topwall. The apertures can
suitably be round, oval or elongate, be it straight or
serpentine. Elongate apertures preferably terminate in
radiussed ends. A mixture of shapes can be employed.

30 Whilst the shape, pattern and number of apertures is at
the discretion of the producer, the apertures preferably
have a minimum diameter of 1mm and particularly at least
1.5mm. The diameter of circular apertures and minor
diameter of non-circular apertures is often not more than

to 12.

5

5mm. It is desirable to employ a symmetrical array of apertures. Suitable patterns include parallel, concentric and/or radial distributions of the apertures. In many instances the number of apertures will be selected in the range of from 3 to 24, and often from 3

Additionally, it is possible for the invention

formulations to be employed without disadvantage in dispensing containers that either contain a mechanism for pressure relief or the apertures of which comprise more than about 15% of the top wall surface area, such as from about 15% to about 80%, or a such-back pressure relief

mechanism in which the platform within the container is linked to an advance rotor wheel or button via an intermediate axially pointing serrated cog that initially advances the platform towards the top wall and subsequently permits it to partially retract.

Having described the instant invention and selected or preferred embodiments thereof in general terms, specific embodiments thereof will now be described in greater detail by way of example only.

Formulation Examples 1 to 15 and Comparisons CP1 to CP12.

The following ingredients were employed in the below-10 mentioned Examples and Comparisons:-

	- 1 1 1	manda nama and	Producer
No	Product description	Trade name and	Producer
		grade	
1	volatile D5 silicone	DC245	Dow Corning
	oil		
2	non-volatile silicone	DC200 350cst	Dow Corning
	oil		
3	Fumed silica	Aerosil 200	Degussa
4	microcrystalline wax	Multiwax 180-M	Witco
5	C18-36 acid	Syncrowax HGLC	Croda
	triglyceride wax		
6	gel -Dimethicone	DC9040	Dow Corning
	elastomer in		
	cyclomethicone		
7	Aluminium zirconium	Reach 908	Reheis
	trichlorhydrex gly		
	[AZAG]		
8	Glyceryl tribehenate	Syncrowax HRC	Croda
	wax	•	
9	non-volatile silicone	DC200 10cst	Dow Corning
!	oil		
10	dextrin palmitate	Rheopearl KL	Chiba Flour
			Milling
11	activated aluminium	Aloxicoll LR	Giulini
			<u> </u>

	chlorohydrate [AACH]		
12	C12-15 alkylbenzoate	Finsolv TN	Finetex
	oil		
13	Castor wax	Castorwax MP80	Caschem
14	C ¹⁸⁻³⁶ acid glycol	Syncrowax ERLC	Croda
	ester wax		
15	gel - dimethicone /	KSG 31	Shin-etsu
	copolyol elastomer in		
	mineral oil		
16	gel - block copolymer	Transgel 110	Aiglon
	in hydrocarbon oil		
17	Isoparaffin oil	Isopar M	Exxon Chemicals
18	Isoparaffin oil	Permethyl 101A	Presperse
19	Mineral oil	Sirius M70	Fuchs
20	Mineral oil	Sirius M40	Fuchs
21	gel - block copolymer	Versagel MD750	Penreco
	in hydrocarbon oil		
22	gel - block copolymer	Versagel ME750	Penreco
	in hydrocarbon oil		
23	gel - block copolymer	Versagel M750	Penreco
	in hydrocarbon oil		
24	gel - block copolymer	Polysynlane Gel	Collaborative
	in hydrocarbon oil		Laboratories
25	Decyl Oleate oil	Cetiol V	Cognis
26	Octyl dodecanol oil	Eutanol G	Cognis
27	Diethylhexyl-2,6-	HallBrite TQ	CP Hall
	naphthalate oil		
28	Butyloctyl Salicylate	HallBrite BHB	CP-Hall
	oil		
29	Glycerol	Glycerol	Sigma Aldrich

The Example and Comparison formulations were made by the following general method in which $:\mbox{-}$

5

10

15

20

25

30

- 1. The waxes and carrier oils were added together in the weight proportions indicated in the respective Table 1 or 2 below, stirred gently and heated until 90-95°C is reached and the waxes have dissolved.
- 2. The block copolymer or elastomer was added and physically stirred in to ensure a uniform temperature throughout the mixture. Heating and mixing was continued at 90-95°C until a homogeneous mixture was obtained.
- 3.Particulate antiperspirant active (ambient temperature) were then added under low shear (1500-2500 rpm) to ensure homogenous mixing without external heating.
- 4. The resultant fluid mixture was then poured into samples of the dispensing container/pack described below and allowed to cool to form a soft solid.

Dispensing Container

The dispensing container into which the Example and Comparison formulations were introduced is described herein with reference to Figure 1 which provides a perspective view.

The container comprises a tubular container [1] of oval transverse cross section for the formulation made from translucent plastic having a base [2] provided with a central aperture acting as a housing an axially mounted thumbwheel [3] which is fixed to an axially extending screw threaded spindle [4]. A platform [5] mounted within the container [1] has a central internally screw threaded axial aperture [6] that engages with spindle [4] a domed upper top wall [7] and a dependent skirt [8] that fits in fluid-tight contact with the interior surface of the sidewall [9] the container [1]. The container [1] is

closed at the end opposite the base [2] by a closure [10] having a domed top wall [11] or respective major and minor diameters of 5.6mm and 31.5mm having a central flattened area [12] which defines three elongate apertures [13] having lateral sides extending in parallel with the major transverse axis of the closure [10] terminating in radiussed ends and an outer area of radius 28mm. The three apertures together constitute 3.6% of the surface area of dome [11], taking into account the curved nature of the dome.

Product Characterisation

Syneresis Score

25

15 The Syneresis Score was determined by visually inspecting filled dispensers that had been subjected to the test method described below. The method was carried out at laboratory ambient temperature, i.e. in the region of 22 to 23°C during the laboratory working day, and falling to between 15 and 20°C overnight.

Samples of dispensing containers according to Figure 1 which had been filled and allowed to cool to ambient in the general preparative method described above were stored for 2 days or until the first working day thereafter and then subjected to one or more cycles of steps a) and b).

In each cycle, in step a) the platform in the dispenser was advanced towards the closure sufficiently to allow

30 approximately 1cm length of extrudate to extrude out through each of the three apertures in the dome of the closure. The extrudate was wiped off the dome using a paper towel. Step a) was carried out four times.

10

15

After the 4th time that step a) had been completed, step b) was carried out, in which the dispenser was stored upright underneath a translucent beaker (to prevent contamination by foreign bodies) on the laboratory bench until the next working day. The domed closure was then examined visually to determine whether there had been any solvent leakage or other observable changes to the pack exterior/interior. Any sign of formulation leakage or other significant change was recorded. Any leakage was wiped off the dispenser using a paper towel.

The cycle of steps a) and b) was repeated for up to a further 5 cycles, i.e. up to a maximum of 6 cycles, each cycle comprising, extrusion and wiping off of formulation four times, storage of the dispenser until the next working day at laboratory ambient temperature and then a visual check and removal of surface material.

20 Each formulation was classified according to its ability to resist leakage as measured by the method described above.

The results are summarised in the Tables below

NnC - no syneresis observed after n cycles - ie a pass 25 SnC - syneresis observed after n cycles - ie a failure

Antiperspirant efficacy

Certain of the Example and comparison formulations were subsequently tested for their antiperspirant efficacy

(sweat reduction) under a standard efficacy test protocol and compared with the efficacy achieved under the same hot room test conditions with a reference soft solid formulation of acceptable efficacy, viz. CP1. The protocol employs a panel of subjects to whom a reference

sample is applied to one armpit and a test sample to the other, with a left/right balance for the two samples. The test enables the relative sweat reduction of the test compared with the reference formulation to be determined

Fail indicated that the sweat reduction achieved was markedly lower than that achieved by application of the reference soft solid CP1, being in the region of 2/3rds or lower. This was considered to be unacceptable.

Pass indicated that the sweat reduction achieved was similar to that from the reference soft solid, ie above 5/6ths and was considered to be acceptable.

15 A blank in subsequent Tables 1 and 2 indicates either the absence of that ingredient or that the particular characterisation has not been carried out.

Viscosity Measurement.

20 For some of the Examples, the viscosity of a dispersion of the block copolymer in the carrier oils in their respective weight ratios was measured at 25°C on a Haake RV20 Rotovisco viscometer using a SV1 cup and bob system, at a constant shear stress of 15 Pa.S. This is shown in Table 2 as Polymer Viscosity

Comparisons CP1 to CP12

Table 1

Comparison No	CP1	CP2	CP3	CP4	CP5	CP6	
Ingredients	% by weight						
Cyclomethicone (1)	55	62.75				26.8	
Dimethicone 350cst (2)	8						
Silica (3)	1			1.5			
MicroXtalline wax (4)	3.25						
Triglyceride wax (5)	3.25	1.25					
Elastomer gel (6)	4						
AZAG (7)	25.5	26					
Glyceride wax (8)		5					
Dimethicone 10cst (9)		5					
Dextrin palmitate (10)			10		3		
AACH (11)			25.5	25.5	25.5	25.5	
Benzoate oil (12)			64.5	63	31.5		
castor wax (13)				7.5		5.625	
glycol ester wax (14)				2.5		1.875	
Elastomer gel (15)					40		
Transgel 110 (16						40.2	
Characterisation							
Syneresis Score *	S1C	S1C	S1C	S1C	N6C	S2C	
Efficacy	Ref			pass	fail		

36 Table 1 (cont)

CP7	CP8	CP9	CP10	CP11	CP12		
% by weight							
18.4							
		25.5	25.5	25.5	25.5		
25.5	25.5						
					36.5		
				36.5			
			36.5				
		36.8					
18.4	44.7						
5.625		5.625	5.625	5.625	5.625		
1.875		1.875	1.875	1.875	1.875		
30.2	29.8	30.2	30.2	30.2	30.2		
Characterisation							
S6C	S1C	S5C	S4C	S1C	S1C		
	18.4 25.5 18.4 5.625 1.875 30.2	18.4 25.5 25.5 1.875 30.2 29.8 haracterisat:	% by w 18.4 25.5 25.5 25.5 36.8 18.4 44.7 5.625 1.875 30.2 29.8 30.2 haracterisation	% by weight 18.4 25.5 25.5 25.5 36.5 36.8 18.4 44.7 5.625 5.625 1.875 1.875 1.875 30.2 29.8 30.2 30.2 haracterisation	% by weight 18.4 25.5 25.5 25.5 36.5 36.8 18.4 44.7 5.625 5.625 5.625 1.875 1.875 1.875 30.2 29.8 30.2 30.2 30.2		

Comparison formulation CP1 was a reference soft solid formulation similar to a formulation that was commercially 5 available in 2001. Formulations in comparisons CP1 to CP4 comprised various carrier fluids and wax structurants, comparisons CP3 and CP4 employing a member of a class of carrier fluids employed in the instant invention. They all had or were expected to have acceptable efficacy, but

- 10 demonstrated a very low resistance to syneresis, because syneresis was observed after the first cycle from a dispenser which did not contain a pressure relief mechanism but which used a domed closure in which the apertures represented below 5% of its surface area.
- 15 CP5 employed a different structurant system but a carrier fluid system comprising an ester oil and a mineral oil that is in accordance with the present invention. Although it

demonstrated good resistance to syneresis, it failed to provide acceptable efficacy.

- Examples CP6 to CP12 all contained a block copolymer, employing a range of solvent systems and combinations with wax structurants. All failed the syneresis test.
- CP6 contained waxes and a volatile silicone. CP7

 10 contained an aromatic ester as well as a significant proportion of volatile silicone. CP8 did not contain a wax. It was very sticky and poured from the dispenser. CP9 to CP12 contained an additional carrier other than an aromatic ester.
- This shows that the presence of the block copolymer as a structurant is not sufficient by itself to ensure non-syneresis, even when employed in a selected carrier oil system or in combination with a wax.

15

Examples 1 - 15

Table 2

<u> </u>							
Example No	1	2	3	4	5	6	
Ingredients	% by weight						
Transgel 110 (16)	40.2	30.2	40.2	30.2	30.2	30.2	
Benzoate oil (12)	26.8	18.4	26.8	18.4	18.4	18.4	
Isoparaffin (17)		18.4					
Isoparaffin (18)				18.4			
Mineral oil (19)					18.4		
Mineral oil (20)						18.4	
Castor wax(13)	5.625	5.625	5.625	5.625	5.625	5.625	
glycol ester wax (14)	1.875	1.875	1.875	1.875	1.875	1.875	
AACH (11)	25.5	25.5					
AZAG(7)			25.5	25.5	25.5	25.5	
Characterisation							
Syneresis Score	N6C	N6C	N6C	Nec	N6C	N6C	
Efficacy	pass	pass	pass				
Polymer Viscosity Pa.s	49.2	3.3	2.9	3.9	2.9		
			·				

39 Table 2 (cont)

Example No	7	8	9	10	11	12	
Ingredients	% by weight						
Transgel 110 (16)						35.2	
Versagel MD750 (21)				40.2	35.2		
Versagel ME750 (22)		40.2					
Versagel M750 (23)			40.2				
Polysynlane Gel (24)	40.2						
Benzoate oil (12)	21.4	26.8	26.8	26.8	15.9	27.3	
Isoparaffin (17)					15.9		
Castor wax (13)	5.625	5.625	5.625	5.625	5.625	9	
glycol ester wax(14)	1.875	1.875	1.875	1.875	1.875	3	
AACH (11)	25.5			25.5		25.5	
AZAG (7)		25.5	25.5		25.5		
Characterisation							
Syneresis Score	N6C	N6C	N6C	N6C	N6C	N6C	
Efficacy				pass			
Polymer Viscosity Pa.s	24.4	14.8	10.1	_	-	-	

Table 2 (cont)

Example No	13	14	15			
Ingredients	% by weight					
Transgel 110 (16)	40.4	27.5	40.2			
Benzoate oil (12)	22.0	27.5	24.8			
Naphthalate oil (27)	5.0					
Salicylate oil (28)		10				
Glycerol			2.0			
Castor wax (13)	5.7	7.5	5.625			
glycol ester wax (14)	1.9	2.5	1.875			
AACH (11)	25.0	25.5	25.5			
Characterisation						
Syneresis Score	N6C	Nec	N6C			

10

40

All Examples 1 to 15 demonstrated improved and acceptable resistance to syneresis compared with related comparison formulations CP6 to CP12. The Example formulations also had acceptable efficacy, that wass similar to reference soft solid CP1, as demonstrated by the results obtained for representative Examples 1, 2, 3 and 10. The efficacy of such Example formulations was markedly superior to the efficacy of Comparison formulation CP5 employing the same classes of carrier oils.

Claims

- A cosmetic composition comprising; at least 60% by weight in total of a water immiscible carrier liquid and structurant system therefor, and from 1 to 30% by weight of a particulate antiperspirant active suspended in said carrier liquid said carrier liquid comprising a mixture of a hydrocarbon oil and an aromatic ester oil in a weight ratio of from 1:2 to 15:1 and said structurant system comprising from 5.5 to 20% in total of a di or triblock alkylene/arylene block copolymer and an organic wax in a weight ratio to each other of from 5:1 to 30:1.
- A cosmetic composition according to claim 1 characterised in that the weight ratio of hydrocarbon oil to aromatic ester oil is at least 2:3 and preferably at least 1:1.
- A cosmetic composition according to either preceding claim characterised in that the weight ratio of hydrocarbon oil to aromatic ester oil is up to 6:1 and preferably up to 4:1.
- A cosmetic composition according to any preceding claim characterised in that the total weight proportion of carrier oils in the composition is at least 45% and preferably at least 55%.
- A cosmetic composition according to any preceding claim characterised in that the total weight proportion of carrier oils in the composition is not more than 80% and preferably not more than 70%.

- A cosmetic composition according to any preceding claim characterised in that the antiperspirant active is an astringent aluminium and/or zirconium salt, preferably a halohydrate.
 - A cosmetic composition according to claim 6 characterised in that the astringent salt is an aluminium and/or zirconium chlorohydrate, optionally activated, and/or an aluminium/zirconium complex with an amino acid.
 - A cosmetic composition according to claim 7 characterised in that the astringent salt is an activated aluminium chlorohydrate or an aluminium zirconium chlorohydrate complexed with glycine.
 - A cosmetic composition according to any one of claims 6 to 8 characterised in that the antiperspirant active is free from hollow particles and has a refractive index which differs from the average refractive index of the carrier liquids by from 0.01 to 0.05 units.
 - 10 A cosmetic composition according to any preceding claim characterised in that the weight ratio of carrier oils to structurant system is within the range of from 6:1 to 10:1.
 - 11 A cosmetic composition according to any preceding claim characterised in that the structurant system comprises at least 6% by weight of the composition.

- 13 A cosmetic composition according to any preceding claim characterised in that the structurant system comprises not more than 12% by weight of the composition.
- 14 A cosmetic composition according to any preceding claim characterised in that the weight ratio or the organic wax to the block copolymer is at least 8:1.
- 15 A cosmetic composition according to any preceding claim characterised in that the weight ratio or the organic wax to the block copolymer is up to 24:1.
- A cosmetic composition according to claim 13 or 14 characterised in that the numerical product obtained by multiplying the weight percentage of organic wax with the weight percentage of the block copolymer is in the range of 4 to 6.5.
- 17 A cosmetic composition according to any preceding claim characterised in that the weight percentage of organic wax in the composition is from 6 to 9%.
- A cosmetic composition according to any preceding claim characterised in that the organic wax comprises one or more waxes selected from hydrocarbon waxes, waxy linear fatty alcohols and esters of fatty acids or mixtures thereof said wax being solid at 40°C.
- 19 A cosmetic composition according to claim 17 characterised in that the wax comprises ester waxes

- 20 derived from fatty acids and glycerol and/or ethylene glycol.
- 21 A cosmetic composition according to any preceding claim characterised in that the arylene/alkylene block copolymer is derived from styrene and butadiene or isoprene or ethylene/butylene or ethylene propylene.
- 22 A cosmetic composition according to any preceding claim characterised in that the block copolymer is introduced into the composition in the form of a pre-dispersion in a hydrocarbon oil.
- 23 A cosmetic composition according to claim 20 characterised in that the concentration of the block copolymer in the pre-dispersion is from 1.5 to 4% by weight.
- 24 A cosmetic composition according to any preceding claim characterised in that a dispersion of the block copolymer in the carrier oils has a viscosity of from 1 to 25 Pa.s when measured at 25°C in a viscometer.
- 25 A cosmetic product comprising an anhydrous soft solid cosmetic composition contained within a dispensing container comprising a chamber for the cosmetic composition provided at one end with a closure defining at least one aperture and with a means for impelling the antiperspirant composition

- 27 towards the cover, in which the cosmetic composition is in accordance with any preceding claim.
- 28 A cosmetic product according to claim 23 characterised in that the dispensing container is free from immediate pressure reducing means.
- 29 A cosmetic product according to claim 23 or 24 characterised in that the at least one aperture constitutes not more than 14% of the surface area of the closure for the dispensing container.
- 30 A cosmetic product according to claim 25 characterised in that the at least one aperture constitutes from 3 to 13% of the surface area of the closure.
- A process of making a cosmetic product comprising a dispensing container comprising a chamber for a cosmetic composition provided at one end with a closure defining at least one aperture and with a means for impelling the antiperspirant composition towards the closure, characterised in that the cosmetic composition is in accordance with any of claims 1 to 22, and the process comprises the steps of:
 - i) forming a mixture of the organic wax and at least a fraction or component of the carrier fluid mixture comprising hydrocarbon oil and/or aromatic ester oil;
 - ii) stirring the mixture and raising its temperature to a temperature selected within the

range of from 50 to 120 °C at which the mixture is homogeneous;

- iii) introducing into the mixture the copolymer, optionally premixed with the remainder of the carrier liquid, stirring the augmented mixture and maintaining or elevating its temperature within the range of up to 120° C until it is homogeneous;
- iv) introducing the particulate antiperspirant with stirring into the homogenous augmented mixture at a temperature above its normal setting temperature;
- v) introducing the resultant antiperspirantcontaining mixture into the chamber of the dispenser and
- vi) cooling the antiperspirant-containing composition or allowing it to cool to below a temperature at which it forms a soft solid.
- A cosmetic method of controlling perspiration comprising applying topically to skin a cosmetic product according to any of claims 23 to 26.

- 47 -

Abstract

Cosmetic Compositions

Cosmetic compositions in the form of soft solids having in combination an improved resistance to syneresis and retained efficacy and which contain a particulate antiperspirant suspended in a water-immiscible carrier liquid structured by a structurant system are obtainable by employing as carrier liquid a mixture of a hydrocarbon oil and an aromatic ester oil in a weight ratio of from 1:2 to 15:1 and as structurant system from 5.5 to 20% in total of a di or triblock alkylene/arylene block copolymer and an organic wax in a weight ratio to each other of from 5:1 to 30:1.

OLUSIN AND IB JENG SIHL

7.

, JII,